



165 MolyXP Universal Extreme Pressure Grease

SDS Revision Date: 09/20/2021

## 1. Identification

Product identifier

Product Identity 165 MolyXP Universal Extreme Pressure Grease

Other means of identification 165

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name: Southwestern Petroleum Lubricants LLC  
3401 Quorum Drive Suite 360  
Fort Worth, Texas 76137

Emergency:

1.4. Emergency telephone number: 734-930-0009

Emergency: numbers call Chemtrec 24/7 USA and  
Canada 1-800-424-9300 or 1-703-527-3887

Customer Service: 800-433-5735

## 2. Hazard(s) identification

Classification of the substance or mixture

## Label elements

H315 Causes skin irritation.

H350 May cause cancer.

### **[Prevention]:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves, eye protection, face protection.

### **[Response]:**

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P308+313 IF exposed or concerned: Get medical advice or attention.

P332+313 IF SKIN IRRITATION OCCURS: Get medical advice or attention.

P362+364 Take off contaminated clothing and wash it before reuse.

### **[Storage]:**

P405 Store locked up.

### **[Disposal]:**

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillate (petroleum) hydrotreated heavy naphthenic CAS Number: 0064742-52-5 Synonyms: Distillate (petroleum) hydrotreated heavy naphthenic, Distillates (petroleum), hydrotreated heavy naphthenic; baseoil-unspecified, Polymer binders and adhesive, Petroleum distillates, hydrotreated heavy naphthenic	40 - 70	Asp. Tox. 1;H304	----
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 0064742-53-6 Synonyms: Distillates (petroleum), hydrotreated light naphthenic, Distillates (petroleum), hydrotreated light naphthenic; baseoil-unspecified	30 - 60	Asp. Tox. 1;H304	----
Polybutene CAS Number: 0009003-29-6 Synonyms: Polybutene	7 - 13	Asp. Tox. 1;H304 Skin Irrit. 2;H315	----
Graphite CAS Number: 0007782-42-5 Synonyms: Graphite	1 - 5	Not Classified	----

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

#### Section 4. First aid measures

##### Description of first aid measures

General                      In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

#### Most important symptoms and effects, both acute and delayed

Overview	<p>If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.</p> <p>Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
----------	--

## Section 5. Fire-fighting measures

### Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Local authorities should be advised if significant spillages cannot be contained.

## Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Storage Temperature: -50 - 50C ( -58 - 122F)

For containers or container linings, use mild steel or high density polyethylene.

Do not use PVC.

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection
--

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0007782-42-5	Graphite	ACGIH	TWA: 2 mg/m <sup>3</sup>
		Alberta	2 mg/m <sup>3</sup> TWA (all forms except Graphite fibres, respirable)
		British Columbia	2 mg/m <sup>3</sup> TWA (all forms except Graphite fibres, respirable)
		Manitoba	2 mg/m <sup>3</sup> TWA (all forms except Graphite fibers, respirable particulate matter)

		New Brunswick	2 mg/m <sup>3</sup> TWA (all forms except graphite fibres)
		Newfoundland and Labrador	2 mg/m <sup>3</sup> TWA (all forms except Graphite fibers, respirable particulate matter)
		Nova Scotia	2 mg/m <sup>3</sup> TWA (all forms except Graphite fibers, respirable particulate matter)
		Northwest Territories	2 mg/m <sup>3</sup> TWA (natural, all forms, except Graphite fibres, respirable fraction) 4 mg/m <sup>3</sup> STEL (natural, all forms, except Graphite fibres, respirable fraction)
		Nunavut	2 mg/m <sup>3</sup> TWA (natural, all forms, except Graphite fibres, respirable fraction) 4 mg/m <sup>3</sup> STEL (natural, all forms, except Graphite fibres, respirable fraction)
		Ontario	2 mg/m <sup>3</sup> TWA (except Graphite fibres, respirable)
		Prince Edward Island	2 mg/m <sup>3</sup> TWA (all forms except Graphite fibers, respirable particulate matter)
		Quebec	2 mg/m <sup>3</sup> TWAEV (containing no Asbestos and <1% Crystalline silica, except Graphite fibres, respi
		Saskatchewan	2 mg/m <sup>3</sup> TWA (natural, except Graphite fibres, respirable fraction) 4 mg/m <sup>3</sup> STEL (natural, except Graphite fibres, respirable fraction)
		Yukon	20 mppcf TWA; 30 mppcf TWA (synthetic); 10 mg/m <sup>3</sup> TWA (synthetic)
0009003-29-6	Polybutene	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit

		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit



		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup> OSHA PEL and 10 mg/m<sup>3</sup> ACGIH.

## Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Skin protection is not required under normal conditions of use. Oil impervious gloves and oil impermeable apron recommended.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

## Section 9. Physical and chemical properties

Appearance	Semi Solid Black, viscous gel Lubricating Grease
Odour	None
Odour threshold	No available information
pH	7.8
Melting point / freezing point	315 C
Initial boiling point and boiling range	No available information
Flash Point	°F °C, Test method: (Open/Close cup)
Evapouration rate (Ether = 1)	Nil
Flammability (solid, gas)	No available information
Upper/lower flammability or explosive limits	<b>Lower Explosive Limit: 0.9</b> <b>Upper Explosive Limit: 7.0</b>

Vapour pressure (Pa)	No available information
Vapour Density	>5
Relative Density	0.95
Solubility in Water	Not miscible in water.
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	330 C
Decomposition temperature	No available information
Viscosity (cSt)	No available information
VOC Content	0.0001
Other information	
DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)	

## Section 10. Stability and reactivity

### Reactivity

Hazardous Polymerization will not occur.

### Chemical stability

Stable under normal circumstances.

### Possibility of hazardous reactions

No available information

### Conditions to avoid

Excessive heat and open flame.

### Incompatible materials

Strong oxidizing agents and acids.

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

<b>Ingredient</b>	<b>Oral LD50, mg/kg</b>	<b>Skin LD50, mg/kg</b>	<b>Inhalation vapour LC50, mg/L/4hr</b>	<b>Inhalation Dust/Mist LC50, mg/L/4hr</b>	<b>Inhalation Gas LC50, ppm</b>
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Polybutene - (9003-29-6)	> 10,000, Rat - Category: NA	No data available	No data available	No data available	No data available

Graphite - (7782-42-5)	> 2,000.00, Rat - Category: 4	No data available	No data available	> 2,000.00, Rat - Category: NA	No data available
------------------------	-------------------------------	-------------------	-------------------	--------------------------------	-------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value
0007782-42-5	Graphite	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0009003-29-6	Polybutene	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable

Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

**Symptoms and effects, both acute and delayed::**

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Treat symptomatically.

Section 12. Ecological information

Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus

Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	Not Available	Not Available	Not Available
Polybutene - (9003-29-6)	> 10,000, Leuciscus idus	101.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata
Graphite - (7782-42-5)	100.00, Danio rerio	> 100.00, Daphnia magna	> 100.00 (72 hr), Pseudokirchnerella subcapitata

#### Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

#### Bioaccumulative potential

Contains components with the potential to bioaccumulate.

#### Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

#### Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### Other adverse effects

No available information

### Section 13. Disposal considerations

#### Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

### Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1 ? 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
Transport hazard class(es)	<b>TDG Hazard Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Environmental hazards			
IMDG	Marine Pollutant: No;		
Special precautions for user	No available information		

Section 15. Regulatory information
------------------------------------

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

**Canadian Domestic Substance List (DSL):**

Distillate (petroleum) hydrotreated heavy naphthenic

Distillates (petroleum), hydrotreated light naphthenic

Graphite

Molybdenum, N,N-bis(C11-14-branched and linear alkyl)carbamodithioate oxo thioxo complexes

Polybutene

Polyethylene



**Canadian Non-Domestic Substance List (NDSL):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date        09/20/2021

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

End of Document