



212 MolyXP Multi-Grade Gear Lube

SDS Revision Date: 09/22/2021

1. Identification

Product identifier

Product Identity 212 MolyXP Multi-Grade Gear Lube

Other means of identification 212

Relevant identified uses of the substance or mixture and uses advised against

See Technical Data Sheet.

Details of the supplier of the safety data sheet

Company Name: Southwestern Petroleum Lubricants LLC
3401 Quorum Drive Suite 360
Fort Worth, Texas 76137

Emergency:

1.4. Emergency telephone number: 734-930-0009

Emergency: numbers call Chemtrec 24/7 USA and
Canada 1-800-424-9300 or 1-703-527-3887

Customer Service: 800-433-5735

2. Hazard(s) identification

Classification of the substance or mixture

Skin Irrit. 2;H315 Causes skin irritation.

Carc. 1B;H350

May cause cancer.

Label elements



Danger

H315 Causes skin irritation.

H350 May cause cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves, eye protection, face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P308+313 IF exposed or concerned: Get medical advice or attention.

P332+313 IF SKIN IRRITATION OCCURS: Get medical advice or attention.

P362+364 Take off contaminated clothing and wash it before reuse.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated heavy paraffinic CAS Number: 0064742-54-7 Synonyms: Distillates (petroleum), hydrotreated heavy paraffinic , Distillates (petroleum), hydrotreated heavy paraffinic; baseoil-unspecified, Petroleum distillates, hydrotreated heavy paraffinic	45 - 70	Carc. 1B;H350	----
1-decene, homopolymer, hydrogenated CAS Number: 0068037-01-4 Synonyms: 1-decene, homopolymer, hydrogenated, Dec-1-ene, homopolymer, hydrogenated	30 - 60	Asp. Tox. 1;H304	----
Polybutene CAS Number: 0009003-29-6 Synonyms: Polybutene	10 - 30	Asp. Tox. 1;H304 Skin Irrit. 2;H315	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Most important symptoms and effects, both acute and delayed	
Overview	<p>Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.</p> <p>Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
Skin	Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0009003-29-6	Polybutene	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit

		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
0064742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
0068037-01-4	1-decene, homopolymer, hydrogenated	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit

	Manitoba	No Established Limit
	New Brunswick	No Established Limit
	Newfoundland and Labrador	No Established Limit
	Nova Scotia	No Established Limit
	Northwest Territories	No Established Limit
	Nunavut	No Established Limit
	Ontario	No Established Limit
	Prince Edward Island	No Established Limit
	Quebec	No Established Limit
	Saskatchewan	No Established Limit
	Yukon	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³ OSHA PEL and 10 mg/m³ ACGIH.

Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Avoid skin contact. Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	Thick Black Liquid
Odour	None
Odour threshold	No available information
pH	7.2
Melting point / freezing point	No available information
Initial boiling point and boiling range	330 C
Flash Point	°F °C, Test method: (Open cup)
Evaporation rate (Ether = 1)	Nil
Flammability (solid, gas)	No available information
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information Upper Explosive Limit: No available information
Vapour pressure (Pa)	No available information
Vapour Density	>5
Relative Density	0.85
Solubility in Water	Not miscible in water.
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
VOC Content	0
Other information	

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in

dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
1-decene, homopolymer, hydrogenated - (68037-01-4)	> 5,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	4,800.00, Rat - Category: NA	No data available
Polybutene - (9003-29-6)	> 10,000, Rat - Category: NA	No data available	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0009003-29-6	Polybutene	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0068037-01-4	1-decene, homopolymer, hydrogenated	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	1B	May cause cancer.
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Treat symptomatically.

Skin Causes skin irritation.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7)	101.00, Pimephales promelas	> 10,000, Daphnia magna	100.00 (72 hr), Pseudokirchneriella subcapitata
1-decene, homopolymer, hydrogenated - (68037-01-4)	Not Available	Not Available	Not Available
Polybutene - (9003-29-6)	> 10,000, Leuciscus idus	101.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1 ? 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
Transport hazard class(es)	TDG Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Environmental hazards			
IMDG	Marine Pollutant: No;		
Special precautions for user	No available information		

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

1-decene, homopolymer, hydrogenated

Distillate (petroleum) hydrotreated heavy naphthenic

Distillates (petroleum), hydrotreated heavy paraffinic

Molybdenum, N,N-bis(C11-14-branched and linear alkyl)carbamodithioate oxo thioxo complexes

Polybutene

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information

SDS Revision Date 09/22/2021

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H350 May cause cancer.

End of Document