



SWEPACO
310

ADVANCED TECHNOLOGY IN LUBRICATION SINCE 1933

Premier Engine Oil

- **Advanced anti-oxidant chemistry reduces high temperature deposits by as much as 50% over conventional oils**
- **Formulated with Moly^{XP} for unsurpassed protection from wear**
- **Exceeds ACEA E9-12, Caterpillar ECF-1, 1A & 3, Cummins CES 20086, 20087, Mack EOS 4.5, Detroit Diesel 93K 222, 93K 223, Mercedes-Benz 228.31, Volvo VDS 4.5 and others**

SWEPACO 310 Premier Engine Oil is a high performance synthetic, multi-grade, long drain engine oil, especially formulated to provide industry leading protection from heat, wear and contaminants.

SWEPACO 310 not only meets, but exceeds, the unique service requirements of diesel engines equipped with low emission systems, such as diesel particulate filters (DPF), exhaust gas recirculation (EGR) and diesel oxidation catalysts (DOC).

To meet the cleanliness challenges of these modern engine systems and ultra-low sulfur diesel fuels, SWEPACO 310 has been carefully formulated to provide:

- Superior engine & filter cleanliness
- Superior oxidation resistance for longer drain service
- Added control of abrasive wear, particularly in liners and top rings
- Backwards compatible with older engines



No compromises here. SWEPACO 310 exceeds the industry's most demanding performance requirements, especially for 2017 and later low emission over-the-road diesel engines.

- High, stable TBN for longer service life and better protection from corrosive gases and contaminants
- Superior film thickness and shear stability

SWEPACO 310 achieves this new level of performance with the very finest *SyntheonTM* synthetic base stock blends and the most advanced additive chemistry, including Moly^{XP}, SWEPACO's proprietary anti-wear/extreme pressure additive and proprietary state-of-the-art anti-oxidant chemistry.

For those who require the absolute best in performance from new generation over-the-road diesel engines, SWEPACO 310 is the very best choice. Because it is backwards compatible, it provides a new generation of protection for older diesel engines, off-road diesel equipment, gasoline engines and mixed fleets.

Protect your engines with the *premium choice* ... SWEPACO 310.

PERFORMANCE

Feature	Benefit
Syntheon™ Synthetic Base Stock Blends	<ul style="list-style-type: none"> • Insure more uniform viscosity over a wide temperature range • Help improve high temperature oxidation and thermal stability • Better low temperature flow characteristics help reduce start-up wear • Extend service life
Multi-Grade	<ul style="list-style-type: none"> • Meets the requirements of more than one viscosity grade, resulting in a lubricant that bears the benefits of both viscosities • Made to lubricate effectively over a wider temperature range than a single grade oil allowing you to keep lubrication simple year-round
Moly^{XP}	<ul style="list-style-type: none"> • Acts as a synergist along with other anti-wear additives to eliminate premature wear and reduce friction • Helps improve fuel economy by reducing friction and drag • Insures protection from extreme pressures
State-of-the-Art Oxidation Inhibitors	<ul style="list-style-type: none"> • Reduce oil thickening and deposits by as much as 50%; extend oil life • Help prevent sludge, varnish and carbon deposits that result from oxidation
TBN Booster/Stabilizer	<ul style="list-style-type: none"> • Increase ability to neutralize harmful acids and corrosives • Lengthen service life
Rust and Corrosion Inhibitor	<ul style="list-style-type: none"> • Builds a chemical bond with the surface to keep moisture and acids from penetrating and attacking the surfaces
Anti-Foam Additive	<ul style="list-style-type: none"> • Can lower oil operating temperatures by 25-50° F by dispersing the foam and releasing the trapped heat
Oiliness Additive	<ul style="list-style-type: none"> • Enables the oil to penetrate the surface for better lubrication
Anti-wear Inhibitor	<ul style="list-style-type: none"> • Helps prevent friction and wear • Helps prevent metal to metal contact
Detergent Additive	<ul style="list-style-type: none"> • Helps keep engine parts clean, neutralizes acids formed during combustion
Dispersant Additive	<ul style="list-style-type: none"> • Helps keep solid contaminants in the oil in colloidal suspension, preventing sludge and varnish deposits on engine parts
Pour Point Depressant Additive	<ul style="list-style-type: none"> • Gives the oil better low temperature flow characteristics • Helps to reduce low temperature start-up wear
Viscosity Index Improver Additive	<ul style="list-style-type: none"> • Less high temperature thinning and low temperature thickening
Saves Fuel	<ul style="list-style-type: none"> • Increased "oiliness" provides anti-friction film to reduce fuel consumption
Long Life	<ul style="list-style-type: none"> • Works harder for a longer period of time thus easing the cost and your worries about waste oil disposal
Lab TecSM Fluid Analysis Program	<ul style="list-style-type: none"> • Maximizes equipment and lubricant life and pinpoints impending problems • Reduces waste

Exceeds Performance Requirements of the Following Specifications:


- Mack EOS 4.5, EO-M Plus, EO-M, EO-L Plus, EO-L
- Volvo VDS 4.5, VDS 3, VDS 2
- Cummins CES 20086, 20087
- Daimler Benz 228.31, 228.3, 228.1
- ACEA E9-12, E-7, E-5, E-3
- CAT ECF-1, ECF-1A, ECF-3, C1P, C1N
- Detroit Diesel 93K 222, 93K 223
- MAN M3275
- JASO DH-1
- Global DHD-1
- DFS 93K218, 93K215, 93K214
- MB P228.31
- MTU Category 2.1
- Renault RLD-4
- DQC 111-10-LA
- Ford WSS-M2C171-F1
- API CK-4/SN

Typical Properties:

SAE Engine Oil Grade.....	5W30.....	10W30.....	15W40
API Spec(s).....	CK4/FA4.....	CK4/FA4.....	CK4
Viscosity, cSt @ 40° C.....	72.26.....	74.13.....	109.06
Viscosity, cSt @ 100° C.....	11.5.....	11.9.....	15.14
Viscosity Index.....	153.....	157.....	144
Pour Point °F/°C.....	-40.....	-40.....	-35C(-31F)
Flash Point °F.....	430.....	430.....	440
Flash Point °C.....	221.....	221.....	227
Lb/Gal.....	7.105.....	7.149.....	7.205
Specific Gravity.....	0.8578.....	0.8572.....	0.8639
TBN.....	11.....	11.....	11
Sulfated Ash, % wt.....	1.....	1.....	1

NOTE: Check for availability of all grades in all market areas.

NOTE: Use 5W30 or 10W30 only for 2017 engines and newer



A Product of SPX Technology™.

... the cutting edge performance SWEPCO Customers have come to expect.



Southwestern Petroleum Lubricants, LLC

Fort Worth, Texas • Phone: (817)332-2336 • Fax: (800)736-5823 • Web: www.swepcolube.com